



Specifications Ledvance LED  
Streetlight Urban Lantern Aluminium  
Black 29W 3945lm 165X65D - 830-840  
CCT | IP66 - Asymmetrical

[View Product](#)

## General Information

|                          |                                                      |
|--------------------------|------------------------------------------------------|
| SKU                      | 251025                                               |
| EAN                      | 4099854246784                                        |
| Manufacturer Code        | 4099854246784                                        |
| Brand                    | Ledvance                                             |
| Manufacturer Name        | URBAN LANTERN ASYMMETRIC 29W ASYM PS 830-840 IP66 BK |
| Any Lamp all-in warranty | 5 Years                                              |
| Average Lifetime (h)     | 100000                                               |

## Technical Information

|                             |                                  |
|-----------------------------|----------------------------------|
| Technology                  | LED Integrated                   |
| Wattage                     | 29W                              |
| Voltage (V)                 | 220-240                          |
| Dimmable                    | Not Dimmable                     |
| Colour Code                 | 830 Warm White, 840 Cool White   |
| Colour temperature (Kelvin) | 3000 Warm White, 4000 Cool White |
| Colour Rendering (Ra)       | 80-89                            |
| Colour of Light             | White                            |
| Light colour options        | CCT                              |
| Luminous Flux (Lumen)       | 3945lm                           |
| Lumen per watt              | 136                              |

|                       |                 |
|-----------------------|-----------------|
| Beam Angle (degree)   | 165x65          |
| Power factor          | >0.90           |
| Product Type Category | LED Streetlight |

## Fixture Information

|                        |                          |
|------------------------|--------------------------|
| Mounting Method        | Post top                 |
| Fixture Connection     | Other                    |
| Optical Cover          | PC (Polycarbonate)       |
| Light Distribution     | Asymmetrical             |
| IP-Rating              | IP66                     |
| Impact Protection (IK) | IK10 - 20 joules         |
| Operating Temperature  | -30 to +50               |
| Colour of the Fixture  | Black                    |
| Housing                | Aluminium                |
| Colour of material     | Black                    |
| Emergency Lighting     | No Emergency Unit        |
| Series                 | URBAN LANTERN ASYMMETRIC |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 417 |
| Diameter (mm) | 395 |

## Sensor Information

## Why Any-lamp?

Type of sensor

No Sensor



Order from the **largest lighting specialist** in Europe



**Customised** quotation



Up to **7 years warranty**



**Easy** return process

